



EGGER BASIC

EGGER BASIC FLOORING 7 & 8 / 31 Classic

TECHNICAL DATASHEET

COREBOARD	HDF swell stopp plus	
PROFILE	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP1 441 087 and EP 1 462 587	
GUARANTEE DOMESTIC AREA	15 years according to Egger Guarantee	13 years according to Egger Guarantee
GUARANTEE COMMERCIAL AREA	5 years according to Egger Guarantee	5 years according to Egger Guarantee
ANTISTATIC PROPERTIES ACCORDING TO EN1815	Yes, <2 kV	
CLASS USE	31	31
EUROPEAN NORM EN13329	 EN 13329-31	 EN 13329-31
BOARD INFORMATION		
FORMAT	Classic	Classic
DIMENSIONS mm [length x width]	1292 X 192	1292 X 192
COMPLETE THICKNESS	7	8
BEVEL	—	—
PACK INFORMATION		
PIECES/PACK	10	8
m ²	2.48m ²	1.99m ²
Kg	15.69	14.46
CLASSIFICATION AND GENERAL REQUIREMENTS ACCORDING EN13329		
ABRASION RESISTANCE ACCORDING EN13329, annex E	AC3(ip≥2000)	
IMPACT RESISTANCE ACCORDING EN13329, annex H	Big ball: ≥500mm Small ball: ≥8 N	
RESISTANCE TO STAINING EN438	Group 1 + 2: level 5 Group 3: level 4	
EFFECT OF FURNITURE LEG ACCORDING TO EN424	No damage shall be visible, when tested with foot Type 0 artefact	
EFFECT OF CASTOR CHAIR ACCORDING TO EN425 (Type W)	No change in appearance or damage	
THICKNESS SWELLING ACCORDING TO ISO24336	≤18%	
TOLERANCE OF TOP LAYER ACCORDING TO EN13329	Length ±0.5mm Width ±0.1mm Thickness ± 0.5mm	
LIGHT FASTNESS ACCORDING EN13329	Grey scale ≥level 4(EN:20105-A02)	
STATIC INDENTATION BY CONSTANT PRESSURE ACCORDING TO EN ISO 24343-1	<0.05	
SURFACE SOUNDNESS ACCORDING EN13329, annex D	≥1,0 N/mm ²	
THERMAL RESISTANCE ACCORDING TO EN12667	0.06m ² K/W	

