## EGGER HOME

EGGER HOME FLOORING 7 & 8 / 31 Classic V4	TECHNICAL DATASHEET	TECHNICAL DATASHEET	
COREBOARD	HDF swell stopp plus		
PROFILE  GUARANTEE DOMESTIC AREA	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue.  Patented as JUST clic! EP1 441 087 and EP 1 462 587  15 years according  13 years according		
	to Egger Guarantee	to Egger Guarantee	
GUARANTEE COMMERCIAL AREA	5 years according to Egger Guarantee	5 years according to Egger Guarantee	
ANTISTATIC PROPERTIES ACCORDING TO EN1815	Yes, <2 kV		
CLASS USE	31	31	
EUROPEAN NORM EN13329	EN 13329-31	EN 13329-31	
BOARD INFORMATION	-11-155-7-51	211 20029 02	
FORMAT	Classic	Classic	
DIMENSIONS mm [length x width]	1292 X 192	1292 X 192	
COMPLETE THICKNESS	7	8	
BEVEL	4	4	
PACK INFORMATION			
PIECES/PACK	10	8	
m <sup>2</sup>	2.48m²	1.99m²	
Kg	15.69	14.46	
CLASSIFICATION AND GENERAL REQUIREMENTS ACCORDING EN13	329		
ABRASION RESISTANCE ACCORDING EN13329, annex E	AC3(ip≥2000)		
IMPACT RESISTANCE ACCORDING EN13329, annex H	Big ball: ≥500mm		
	Small ball: ≥8 N		
RESISTANCE TO STAINING EN438	Group 1 + 2: level 5		
	Group 3: level 4		
EFFECT OF FURNITURE LEG ACCORDING TO EN424	No damage shall be visible, when tested with foot Type 0 artefact		
EFFECT OF CASTOR CHAIR ACCORDING TO EN425 (Type W)	No change in appearance or damage		
THICKNESS SWELLING ACCORDING TO ISO24336	≤18%		
TOLERANCE OF TOP LAYER ACCORDING TO EN13329	Length ±0.5mm		
	Width ±0.1mm		
LIGHT FACTURES ACCORDING THACCO	Thickness ± 0.5mm		
LIGHT FASTNESS ACCORDING EN13329	Grey scale ≥level 4(EN:20105-A	02)	
STATIC INDENTATION BY CONSTANT PRESSURE ACCORDING TO	<0.01		
EN 13329			
SURFACE SOUNDNESS ACCORDING EN13329, annex D	≥1,0 N/mm²		
THERMAL RESISTANCE ACCORDING TO EN12667	0.07m² K/W	Settle-Over David Like efficiency	







