

LazyLawn Technical Specification



Description	LazyLawn LL-20	LazyLawn LL-35
Application	Landscape, Garden Lawns, Balconies, Play areas etc.	Landscape, Garden Lawns, Balconies, Play areas etc.
Pile Content	U.V. Resistance PE Monofilament & curly yarn	U.V. Resistance PE Monofilament & curly yarn
Colors	4 tone	4 tone
Yarn Count(Dtex)	7500	7500
Yarn Height(mm)	20 (±2mm)	35 (±2mm)
Machine gauge	3/8inch	3/8inch
Tufts per running metre	160	160
Density of Grass **	16800 tufts/m2	16800 tufts/m2
Yarn Weight(g/m²)	610	990
Drain holes per square	50	50
Total Weight (g/m²)	2,010 (+-5%)	2,390 (+-5%)
Primary Backing	UV Resistant PP woven-clothes	UV Resistant PP woven-clothes
Secondary Backing	UV Resistant (PP)	UV Resistant (PP)
Coating backing	Latex+rubber Styrene-Butadiene Basis,	Latex+rubber Styrene-Butadiene Basis,
Full Roll size(m) 2m wide	2m wide x 25m long	2m wide x 25m long
Full Roll size(m) 4m wide	4m wide x 25m long	4m wide x 25m long
Warranty	8 years	8 years

**** DENSITY is the key factor in the specification as that determines the quality and life of the grass. It's also important to check out the backing to ensure that its substantial and that the tufts are all properly secured and protected.**